

Ms. Stephanie Stumbo Public Service Commission 211 Sower Boulevard P. O. Box 615 Frankfort, Kentucky 40601

RECEIVED

APR 0 1 2008

PUBLIC SERVICE
COMMISSION

Louisville Gas and Electric Company

State Regulation and Rates 220 West Main Street PO Box 32010 Louisville, Kentucky 40232 www.eon-us.com

Martin J. Reinert Senior Regulatory Analyst T 502-627-4173 F 502-627-3213 marty.reinert@eon-us.com

April 1, 2008

RE:

Case No. 2000-00278

Case No. 2002-00262

Mark of Beier

Gas Meter Performance Control Plan Residential Service Regulator Inspection and Replacement Program

Dear Ms. Stumbo:

Pursuant to the above mentioned cases, Louisville Gas and Electric ("LG&E") hereby files 5 copies of the annual report.

If you have any questions please do not hesitate to contact me.

Sincerely,

Marty J. Reinert

Enclosure

Louisville Gas & Electric Gas Meter Performance

Control Plan Year 2007

RECEIVED

APR 0 1 2008

PUBLIC SERVICE COMMISSION



Year 2007 Gas Meter Sampling Plan Results

I. Introduction

The 2007 LG&E Gas Meter Performance Control Program required 7,924 gas meters within 143 control groups to be tested and their accuracy performance documented.

Any sampled meter which proof tested beyond +/- 2% (fast or slow) was considered to be a failed meter. The control groups sampled during 2007 performed extremely well. Two (2) small control groups of the Rockwell 250 model failed the sampling criteria. Combined, the two failed control groups total 1,001 gas meters and are scheduled to be removed by July 1, 2009. This report summarizes the results of the 2007 LG&E Gas Meter Sampling Program.

II. Meter Performance

The meter groups were separated into three capacity classifications. Meters with capacities up to and including 500 CFH, which primarily represent residential meters, represented the largest group with eighty-nine (89) control groups and 6,861 meters. Meters with capacities that range from 501 CFH to 1500 CFH (Commercial), represented the second largest group with forty-six (46) control groups and 871 meters. Meters with capacities 1501 CFH (Industrial) and above comprised the balance of the sampling with eight (8) control groups and 192 meters.

A summary of each control group, along with statistical analysis data, is shown in appendix A. The definitions of selected statistical categories are included.

Of the 143 control groups sampled, 141 passed the sampling criteria in 2007. A total of eleven (11) control groups had their remaining population removed through the sampling program in 2007.

A. Residential Class - Up to and including 500 cfh

1. Strong Performing Groups - Reduced Sampling

The strongest performing meter groups in this capacity continue to be the American AL175, AL250, AC250, and the AL425. Of the 1,454 meters in the twenty-two (22) control groups of AL175 meters, only twenty (20) individual meters failed the sampling criteria, a 1.38 percent failure rate. The eighteen (18) AC250 control groups had a total of twelve (12) failures out of the 1,206 meters tested, a 1.00 percent failure rate. The ten (10) AL425 control groups totaling 290 meters experienced six (6) failures, a 2.07 percent failure rate.

The American Meter Company AL175 and AC250 residential models were the primary types of gas meters LG&E either purchased new or had remanufactured and placed back into the system, which continues to improve the overall accuracy of the installed meter population.

The one (1) American AL250 control group totaling thirty-two (32) meters experienced zero (0) failures. Although this model performs well, it is being phased out as the meters are removed due to the small number of this model installed.

Test results were analyzed for the below groups to verify each model did not exceed the Limit Numbers For Reduced Inspection, Table VIII, under the American Standard – Sampling Procedures and Tables For Inspection By Attributes guidelines.

Model 033 – American AL175 CFH
Last 10 Control Group Years Tested = 740 Meters Tested
Limit Number For Reduced Testing - 25
Actual Deviate Meters – 9

Model 33A – American AL175 CFH
Last 10 Control Group Years Tested = 506 Meters Tested
Limit Number For Reduced Testing - 25
Actual Deviate Meters – 4

Model 015 – American AL425CFH
Last 10 Control Group Years Tested = 290 Meters Tested
Limit Number For Reduced Testing – 8
Actual Deviate Meters – 6

Model 078 – American AC250 CFH
Last 10 Control Group Years Tested = 644 Meters Tested 692
Limit Number For Reduced Testing - 25
Actual Deviate Meters – 4

The below models will remain on Reduced Sampling in year 2008.

American Model AL175 Model Code 033 American Model AL175 Model Code 33A American Model AL425 Model Code 015 American Model AC250 Model Code 078

2. Weak Performing Residential Group

The older models of Rockwell residential class 250 CFH meters continue to be the poorest performing control groups. Of the four (4) Rockwell R250 Code 057 control groups consisting of 242 meters sampled this year, thirty-four (34) of the individual meters failed the sampling criteria for a 14.05 percent failure rate. Two of the 057 control groups, years 1988 and 1989, failed the sampling criteria and have been scheduled for removal by July 1, 2009. LG&E intends to make a concerted effort to remove the failed 057 meters well ahead of the removal deadline.

Rockwell R250 gas meters removed from the system are being replaced by the better performing model of the American AC250 gas meter.

The Rockwell 175 CFH meters continue to be one of the weaker performing control groups. Of the seventeen (17) Rockwell R175 control groups consisting of 2,830 meters sampled this year, ninety (90) of the individual meters failed the sampling criteria for a 3.18 percent failure rate.

The Actaris 250 Metris, size code 018, gas meter performed below expectations, becoming one of the weaker performing control groups. The three (3) control groups tested this year experienced fifteen (15) failures out of 312 meters tested, a 4.81 percent failure rate. LG&E does not recycle the Actaris Metris 250. When it is removed from service it is currently being replaced with an American AC250 gas meter.

B. Commercial Class - 501 cfh up to and including 1500 cfh

Forty-six (46) control groups in the Commercial Meter Class were tested in 2007 and there were no control group failures.

The strongest performing meters in this class was the American AL1400 meter which experienced zero (0) individual meter failures within the eight (8) control groups tested and the Rockwell #3 Emco which also experienced zero (0) individual meter failures within the seven (7) control groups tested.

Demonstrating acceptable performance were the Rockwell R750 control groups with six (6) meter failures out of 256 meters tested, and the American AL1000 control groups which had eleven (11) meter failures out of 230 meters tested.

Beginning in the 2003 test year, all Commercial Class Control Groups, regardless of whether they meet the Limit Numbers For Reduced Inspection, Table VIII, under the American Standard – Sampling Procedures and Tables For Inspection By Attributes guidelines, have been placed on the Single Sampling Plan For Normal Inspection due to the small volume of meters in the Commercial Class Control Groups.

C. Industrial Class - Over 1500 cfh

The eight (8) control groups in this capacity range performed extremely well and no groups failed the sampling criteria. Two of the control groups were exhausted by the 2007 Sampling Program. The six (6) control groups not exhausted in the 2007 Sample Program, had only two (2) individual meters exceed the sampling accuracy criteria.

Beginning in 2003 test year, all Industrial Class control groups, regardless of whether they meet the Limit Numbers For Reduced Inspection, Table VIII, under the American Standard – Sampling Procedures and Tables For Inspection By Attributes guidelines, have been placed on the Single Sampling Plan For Normal Inspection due to the small volume of meters in the Industrial Class control groups.

D. 2007 Failed Group Summary

Two (2) control groups of the Rockwell 250 model failed the 2007 sampling criteria.

Table 1: 2007 Failed Meter Groups To Be Removed By July 1st, 2009

			Installed	Beginning	Remaining
Manufacturer	Model	Type	Year	Population	Population
Rockwell	R 250	057	1988	638	534
Rockwell	R250	057	1989	568	467

III. Safety

As part of the LG&E Meter Sampling change-out activities, safety inspections were performed and "red-tags" were issued when deficiencies were found which resulted in a customers appliance being left off or the customers gas service partially or fully suspended until the deficiency was corrected by the customer. The results of these safety inspections directly associated with LG&E's Meter Sampling Program is summarized in Table 2 below.

Table 2: Year 2007 Safety Inspection Results

Type of Problem/Appliance	# of "Red Tags"
Water Heater Not Venting Correctly/Leaks/Othe	er 9
Houseline Leak -left off at meter	8
Obsolete Appliance flexible hook-up lines, etc;)	9
Furnace Problem (internal leak, various Problems	s) 10
Water Heater Leak On Gas Line	1
Leak On Line To Garage	1
Clothes Dryer Leaking	3
Cook Stove Problems	4
Gas Grill – Gas Line Leaking	1
Gas Fireplace Valve Leaking	1
Flex line Through Wall Of Furnace	39

Additionally, 2,558 Customer Surveillance Notices were issued to customers to correct outside deficiencies on their meter loop or exposed outside gas piping.

Table 3: Year 2007 Customer Surveillance Notices Issued

Type Of Customer Notice Issued	Number Issued
Corrosion / Rust On Outside Meter Loop & Associated Piping	2,014
Tree / Shrubbery Growing Inside / Against Meter Loop	53
Gas Piping Not Properly Supported	330
Meter Loop Too Low - In Contact With Soil / Pavement	34
Meter Not Protected From Vehicular Damage	76
Customer Built Over Service Line / Around Meter	2
Service riser piping in contact with pavement	3
Other	46

IV. Year 2007 Residential Meter Sampling Savings				
Table 4, which highlights the estimated savings between a periodic change schedule and the LG&E Gas Meter Performance Control Program for the purchase of new/remanufactured residential class gas meters, is included on the next page.				
·				

2007 Residential Class Meter Sampling Table 4: **Program Estimated Savings**

Metering Savings: Residential Gas Meters	
Periodic Program Costs (10-year Program):	
Number of Meters under Periodic Program [1]	30,691
Unit Remanufacture Cost – Average Blended Cost	\$ 26.31
Residential Meter Costs Under Periodic Program	\$807,480
Sampling Program Costs: [2]	
Number of Meters under Sampling Program	6,861
Number of poor performing meters scrapped	1,070
Number of Meters for Remanufacture	5,791
Remanufactured Meters	5,791
Average Unit Remanufacture Cost – All Models	\$26.31
Remanufactured Meter Costs	\$152,361
Replacement Meters (including FST Replacements)	1,713
Average Replacement Meter Cost (per unit)	\$ 51.90
Replacement Meter Costs	\$88,904
Total Meter Costs Under 2007 Program	\$241,265
Meter Cost Savings From 2007 Program	\$566,215

Administrative and Development Costs:		
Programming Development Costs: [3]		
Number of Hours in Programming	40	
Pay Rate with Overheads	\$ 67.28	
Development Costs	\$ 2,691	
Additional Administrative Costs (Supervisory): [4]		
Total Hours (based on 10 hrs/week)	520	
Pay Rate with Overheads	\$ 49.13	
Additional Admin. Costs	\$25,547	
Total Administrative & Development Costs	\$28,238	

Net 2007 Residential	Meter (Cost S	Savings	\$537,977

^[1] Residential meters on line end of year 1997
[2] Includes 2007 sample meters and any failed meter groups.
[3] Development time for revisions to an Access Database.
[4] Estimated Hours Spent Specific On Administration & Reporting Functions

APPENDIX A

Control Group Data/Analysis

Control Group Test Data Range

Frequency Histograms (Examples)

Statistical Definitions

MEDIAN

The median is the number in the middle of a set of numbers; that is, half the numbers have values that are greater than the median and half have values that are less.

STANDARD DEVIATION

The standard deviation is a measure of how widely values are dispersed from the average value (the mean).

SKEWNESS

Skewness characterizes the degree of asymmetry of a distribution around its mean. Positive skewness indicates a distribution with an asymmetric tail extending towards more positive values. Negative skewness indicates a distribution with an asymmetric tail ending towards more negative values.

CONFIDENCE

The confidence interval is a range on either side of a sample mean. For example, if you order a product through the mail, you can determine, with a particular level of confidence, the earliest and latest the product should arrive.

Test Year 2007 American AL425 Control Group-Installed Year 425 CFH 2005 2003 1999 2001 1998 1997 1996 1995 1994 1993 Code: 015 Reduced Sample Plan 32 32 32 32 32 32 32 32 32 2* Sample Size 596 402 645 538 506 678 221 603 100 13 Original Population 0 0 0 0 0 0 2 2 1 0 # of Slow Failures 0 0 0 0 1 0 0 0 0 # of Fast Failures 0 0 0 0 0 2 1 1 2 0 Total Failures: 5 5 5 5 5 5 5 5 0 Accept Level 8 8 8 8 8 8 8 8 8 Reject Level Pass Pass Pass Pass Pass Pass Pass Pass Pass **Pass** Pass/ Fail? Exhaust If Failed - Remove By: -0.890625 -0.470313 -0.628125 -0.521875 -0.429688 -0.640625 -0.498438 Statistical Data: -0.275 | -0.371875 | -0.485938 Mean (Average Proof) -0.5-0.55-0.375 -0.525 -0.725-0.625-0.85-0.5-0.275 -0.225 Median 0.427386 0.590497 0.4020991 0.673213 0.791982 0.613417 0.805048 0.767845 0.728115 1.732412 Standard Deviation 0.182659 0.161683 0.348687 0.453216 0.627235 0.37628 0.589587 0.648102 3.00125 0.530151 Sample Variance 0.63099 -0.264759 -0.216135 0.665153 0.06542 1.387525 0.229363 -1.150711 -1.291479 NA Skewness -1.1 -1.65 -1.65-1.75 -1.9 -3.6 -1.9-2.25 -2.5 -1.5Minimum 0.65 0.2 0.6 1.25 0.95 2.35 1.05 0.8 1.5 0.95 Maximum 32 32 32 32 32 32 32

0.28554

0.22116 | 0.242719 | 0.212897 | 0.144972 | 0.154089

32

Count

32

^{0.262513 | 0.290251 | 0.276838} 15.5651 Confidence Level(95.0%) * Population less than required 32 minimum sample size - all meters to be changed - Single Sampling Plan For Normal Inspection used to obtain sample size to determine if control passed or failed.

Year 2007

Code & Year:	1993
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	0
4 to .4	0
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	
2.8 to 3.6	0
GT 3.6	0
Total	2

Code & Year:	1994
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	1
-1.2 to4	7
4 to .4	19
.4 to 1.2	3
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1995
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	3
-1.2 to4	15
4 to .4	9
.4 to 1.2	4
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Meter Code 015 American AL 425

Code & Year:	1996
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	1
2 to -1.2	5
-1.2 to4	17
4 to .4	7
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	18
4 to .4	9
.4 to 1.2	2
1.2 to 2.0	0
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	32

1998
umber
0
0
0
4
17
10
1
0
0
0
0
32

Code & Year:	1999
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	6
-1.2 to4	11
4 to .4	13
.4 to 1.2	2
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	2001
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	4
-1.2 to4	11
4 to .4	15
.4 to 1.2	2
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32


Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	21
4 to .4	8
.4 to 1.2	0
1.2 to 2.0	C
2.0 to 2.8	C
2.8 to 3.6	C
GT 3.6	C
Total	32
<u> </u>	

Code & Year:	2005
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	20
4 to .4	11
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Year 2007

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	4
2 to -1.2	29
-1.2 to4	137
4 to .4	101
.4 to 1.2	17
1.2 to 2.0	0
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	290

Meter Code 015 American AL 425



Metris 250

Test Year 2007

Metris 250	lest year 2007				 	 	
250 CFH		Control Gro	up-Installed Ye	ear	 		
Code: 018	2001	2003	2005				
Sample Plan	Single	Single	Single				
Sample Size	80	200	32				
Original Population	905	5492	55				
# of Slow Failures	0	13	1				
# of Fast Failures	0	1	0				
Total Failures:	0	14	1				
Accept Level	10	21	5				
Reject Level	11	22	6				
Pass / Fail?	Pass	Pass	Pass				
If Failed - Remove By:							
Statistical Data:							
Mean (Average Proof)	-0.22375		-0.9	1		İ	
Median	-0.15	-0.9	-0.75	1			
Standard Deviation	0.603155	1	0.594871				
Sample Variance	0.363796		0.353871	ł .			
Skewness	0.243638	0.28154					
Minimum	-1.4	-3.5	-2.2	1			
Maximum	1.6	3.45					
Count	80	200					
Confidence Level(95.0%)	0.134226	0.128172	0.214474				<u> </u>

Test Year 2007

Meter Code


018

Metris 250

Code & Year:	2001	Code & Year:	2003
Data Range	Number	Data Range	Numbe
_T -3.6	0	LT -3.6	
3.6 to -2.8	0	-3.6 to -2.8	
-2.8 to2	0	-2.8 to2	
2 to -1.2	2	2 to -1.2	5
-1.2 to4	28	-1.2 to4	7
-,4 to .4	39	4 to .4	4
.4 to 1.2	10	.4 to 1.2	1
1.2 to 2.0	1	1.2 to 2.0	
2.0 to 2.8	0	2.0 to 2.8	
2.8 to 3.6	0	2.8 to 3.6	
GT 3.6	0	GT 3.6	
Total	80	Total	20

Code & Year:	2005
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	9
-1.2 to4	16
4 to .4	6
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32


Code & Year:	Totals
Data Range	Number
LT -3.6	0
-3.6 to -2.8	5
-2.8 to2	9
2 to -1.2	65
-1.2 to4	115
4 to .4	90
.4 to 1.2	26
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	1
GT 3.6	0
Total	312



Year 2007 Metris 250 TC Control Group-Installed Year 175 CFH 2002 Code: 18T Single Sample Plan 80 Sample Size 801 Original Population # of Slow Failures 4 0 # of Fast Failures Total Failures: 10 Accept Level 11 Reject Level Pass / Fail? Pass If Failed - Remove By: Statistical Data: -0.7375 Mean (Average Proof) -0.65 Median 0.839209 Standard Deviation 0.704272 Sample Variance -1.112437 Skewness -4.7 Minimum 1.55 Maximum 80 Count 0.186757 Confidence Level(95.0%)

Same of

ode & Year:	2002		Code & Year:	Totals
Data Range	Number		Data Range	Number
T -3.6	1		LT -3.6	1
3.6 to -2.8	0		-3.6 to -2.8	0
2.8 to2	3		-2.8 to2	3
.2 to -1.2	12		2 to -1.2	12
1.2 to4	35		-1.2 to4	35
.4 to .4	25		4 to .4	25
4 to 1.2	3		.4 to 1.2	3
1.2 to 2.0	1	1	1.2 to 2.0	1
2.0 to 2.8	0		2.0 to 2.8	0
2.8 to 3.6	0	1	2.8 to 3.6	0
GT 3.6	0]	GT 3.6	0
Total	80		Total	80



Test Year 2007 Actaris 400A

Actaris 400A	Test Year 2007					 			
400 CFH		Control Grou	ıp-installed	Ye	ar	 			
Code: 022	2003	2005		Ц					
Single or Double (S or D)	Single	Single							
Sample Size	8*	1*							
Original Population	26	1							
# of Slow Failures	0	0							
# of Fast Failures	0	0		Ц					
Total Failures:	0	0							
Accept Level	1	0							
Reject Level	2	1							
Pass / Fail?	Pass	Pass							
If Failed - Remove By:	Exhaust	Exhaust							
Statistical Data:									
Mean (Average Proof)	-0.025	0.15							
Median	0.025	0.15							
Standard Deviation	0.205287	NA							
Sample Variance	0.042143	NA							
Skewness	0.495379	NA							
Minimum	-0.3	0.15							
Maximum	0.35	0.15							
Count	8	1							
Confidence Level(95.0%)	0.171624	NA		Ш		 lan For Norma	<u> </u>	1	<u> </u>

^{*} Population less than required 32 minimum sample size - all meters to be changed - Single Sampling Plan For Normal Inspection used to obtain sample size to determine if control passed or failed.


Year 2007

Meter Code 022 Actaris 400A

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	0
4 to .4	8
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2005
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	0
4 to .4	1
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	1

Code & Year:	Total
Data Range	Number
LT -3.6	0
3.6 to -2.8	0
2.8 to2	0
2 to -1.2	0
-1.2 to4	0
4 to .4	9
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	
2.8 to 3.6	0
GT 3.6	0
Total	9



Rockwell R175	Year 2007																
175 CFH		Control Gro	oup-Installed Y	'ear													
Code: 024	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2001	2003	2005
Sample Plan	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single
Sample Size	200	200	125	200	200	200	200	200	200	200	125	80	125	125	125	125	200
Original Population	4664	4440	3080	4587	3845	4441	4948	5196	3869	3680	1788	901	1433	2269	1494	2609	3834
# of Slow Failures	2	5	3	4	3	1	10	16	6	1	3	2	1	1	o	1	3
# of Fast Failures	4	2	0	6	2	6	2	0	3	1	1	۵	0	0	0	11	0
Total Failures:	6	7	3	10	5	7	12	16	9	2	4	2	1	1	0	2	3
Accept Level	21	21	14	21	21	21	21	21	21	21	14	10	14	14	14	14	21
Reject Level	22	22	15	22	22	22	22	22	22	22	15	11	15	15	15	15	22
Pass / Fail?	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
If Failed - Remove By:																	
Statistical Data:																	
Mean (Average Proof)	0.24925	-0.029	-0.032	0.0765	0.0495	0.34775	-0.203	-0.32475	0.01725	-0.104	-0.3508	-0.22125	-0.2192	-0.196	-0.1408	-0.0956	-0.13275
Median	0.25	-0.05	0.05	0.1	0.1	0.35	-0.1	-0.025	0.05	-0.05	-0.35	-0.175	-0.2	-0.1	-0.15	-0.05	-0.05
Standard Deviation	0.97019	0.935553	0.871373	1.097106	0.855957	0.929923	1.131733	1.144563	0.965206	0.786081	0.865629	0.812551	0.736403		0.620724	0.781103	0.765766
Sample Variance	0.941268	0.87526	0.75929	1.203641	0.732663	0.864756	1.28082	1.310025	0.931623	0.617924	0.749314	0.660239			0.385298	0.610122	0.586397
Skewness	-0.931228	-0.340165	-0.605698	0.423119	0.002023	0.019401	-1.142619	-1.168118	-1.019064	0.451432	-0.230298	-0.569479	0.104674		0.089992	-0.017022	-1.727621
Minimum	-5.3	-3.15	-3.05	-4.9	-2.4	-2.2	-6.15	-4.7	-4.5	-2.25	-3.85	-2.8	-2.6		-1.6	-2.95	-4.45
Maximum	2.45	2.75	1.85	5.95		3.05		1.95	3.05				1.9	1	1.75	3.1	1.5
Count	200	200	125	200	200	200	200	200	200	200	125	80	125		125	125	200
Confidence Level(95,0%)	0.135282	0.130452	0.154261	0.152979	0.119353	0.129667	0.157807	0.159596	0.134587	0.10961	0.153244	0.180824	0.130367	0.130347	0.109888	0.13828	0.106777

Meter Code

024

Rockwell R175

Code & Year:	1986
Data Range	Number
LT -3.6	1
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	8
-1.2 to4	32
4 to .4	80
.4 to 1.2	46
1.2 to 2.0	28
2.0 to 2.8	4
2.8 to 3.6	0
GT 3.6	0
Total	200

Code & Year:	1987
Data Range	Number
LT -3.6	0
-3.6 to -2.8	3
-2.8 to2	2
2 to -1.2	15
-1.2 to4	36
4 to .4	83
.4 to 1.2	46
1.2 to 2.0	13
2.0 to 2.8	2
2.8 to 3.6	0
GT 3.6	0
Total	200

Code & Y	ear:	1988
Data Ra	nae	Number
LT -3.6	1	0
-3.6 to -	2.8	1
-2.8 to -	.2	2
2 to -1	2	9
-1.2 to -	.4	19
4 to .4		56
.4 to 1.2		31
1.2 to 2.0		7
2.0 to 2.8		0
2.8 to 3.6		0
GT 3.6		0
Total		125

Code & Year:	1989
Data Range	Number
LT -3.6	1
-3.6 to -2.8	1
-2.8 to2	2
2 to -1.2	12
-1.2 to4	43
4 to .4	73
.4 to 1.2	49
1.2 to 2.0	13
2.0 to 2.8	4
2.8 to 3.6	0
GT 3.6	2
Total	200

Code & Year:	1990
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	3
2 to -1.2	10
-1.2 to4	43
4 to .4	76
.4 to 1.2	55
1.2 to 2.0	11
2.0 to 2.8	1
2.8 to 3.6	1
GT 3.6	0
Total	200

Code & Year:	1991
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	9
-1.2 to4	28
4 to .4	74
.4 to 1.2	57
1.2 to 2.0	25
2.0 to 2.8	4
2.8 to 3.6	2
GT 3.6	0
Total	200

Code & Year:	1992
Data Range	Number
LT -3.6	2
-3.6 to -2.8	4
-2.8 to2	4
2 to -1.2	17
-1.2 to4	40
4 to .4	83
.4 to 1.2	39
1.2 to 2.0	9
2.0 to 2.8	1
2.8 to 3.6	1
GT 3.6	0
Total	200

1993
Number
3
4
9
22
34
75
49
4
0
0
0
200

Code & Year	: 1994
Data Range	Number
LT -3.6	2
-3.6 to -2.8	1 3
-2.8 to2	3
2 to -1.2	g
-1.2 to4	34
4 to .4	88
.4 to 1.2	49
1.2 to 2.0	11
2.0 to 2.8	2
2.8 to 3.6	
GT 3.6	
Total	200
h	

Code & Year:	1995
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	13
-1.2 to4	53
4 to .4	90
.4 to 1.2	37
1.2 to 2.0	5
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	1
Total	200

Meter Code

024

Rockwell R175

Code & Year:	1996
Data Range	Number
LT -3.6	1
-3.6 to -2.8	2
-2.8 to2	0
2 to <i>-</i> 1.2	13
-1.2 to4	38
4 to .4	54
.4 to 1.2	12
1.2 to 2.0	4
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	125
1000	

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	6
-1.2 to4	23
4 to .4	32
.4 to 1.2	15
1.2 to 2.0	2
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1998
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	10
-1.2 to4	34
4 to .4	66
.4 to 1.2	8
1.2 to 2.0	6
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	125


Code & Year:	1999
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	7
-1.2 to4	34
4 to .4	58
.4 to 1.2	23
1.2 to 2.0	2
2.0 to 2.8	
2.8 to 3.6	0
GT 3.6	0
Total	125

Code & Year:	2001
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	7
-1.2 to4	33
4 to .4	61
.4 to 1.2	22
1.2 to 2.0	2
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	125

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	0
2 to -1.2	10
-1.2 to4	24
4 to .4	65
.4 to 1.2	20
1.2 to 2.0	4
2.0 to 2.8	0
2.8 to 3.6	1
GT 3.6	0
Total	125

1	
Code & Year:	2005
Data Range	Number
LT -3.6	2
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	9
-1.2 to4	45
4 to .4	105
.4 to 1.2	33
1.2 to 2.0	5
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	200
·	

Code & Year:	Totals
	_
Data Range	Number
LT -3.6	12
-3.6 to -2.8	17
-2.8 to2	33
2 to -1.2	186
-1.2 to4	593
4 to .4	1219
.4 to 1.2	591
1.2 to 2.0	151
2.0 to 2.8	19
2.8 to 3.6	6
GT 3.6	3
Total	2830




Year 2007 American AL 250 Control Group-Installed Year 250 CFH 1992 Code: 030 Single Sampling Plan Sample Size 32 Original Population 165 # of Slow Failures 0 # of Fast Failures 0 Total Failures: 5 Accept Level Reject Level Pass/ Fail? Pass If Failed - Remove By: Statistical Data: -0.404688 Mean (Average Proof) -0.325 Median 0.498119 Standard Deviation 0.248122 Sample Variance -0.890795 Skewness -1.9 Minimum 0.45 Maximum 32 Count 0.179591 Confidence Level(95.0%)

Sangar , and

Meter Code

030 American AL250

ode & Year:	1992	Code & Year:	Total
Data Range	Number	Data Range	Number
T -3.6	0	LT -3.6	0
3.6 to -2.8	0	-3.6 to -2.8	0
2.8 to2	0	-2.8 to2	0
2 to -1.2	2	2 to -1.2	2
1.2 to4	11	-1.2 to4	11
.4 to .4	18	4 to .4	18
4 to 1.2	1	.4 to 1.2	1
.2 to 2.0	0	1.2 to 2.0	0
2.0 to 2.8	0	2.0 to 2.8	0
2.8 to 3.6	0	2.8 to 3.6	0
GT 3.6	0	GT 3.6	0
Γotal	32	Total	32
	<u> </u>		



Year 2007 American AL175 2003 2005 Control Group-Installed Year 2001 1996 1997 1998 1999 175 CFH 1994 1995 1990 1991 1992 1993 1989 Reduced 1987 1988 Reduced 1985 1986 Reduced Reduced Reduced Reduced Code: 033 Reduced Reduced Reduced Reduced Reduced Reduced Reduced Reduced 50 Reduced Reduced 80 50 Reduced Reduced 80 80 80 Sample Plan 80 80 80 80 80 80 80 80 50 32 50 50 Sample Size 2405 2897 4747 6001 8818 5537 9005 8401 8407 8093 8196 8343 2439 6896 3943 983 1368 2025 Original Population 0 0 0 0 1 2 0 2 2 2 0 0 0 n ٥ # of Slow Failures 1 n 0 0 0 n 0 0 Λ 2 0 0 0 # of Fast Failures 0 2 2 0 2 3 0 2 0 0 2 Total Failures: 7 10 7 10 10 10 10 10 10 10 10 10 7 10 5 10 13 10 7 7 13 13 13 Accept Level 13 13 13 13 13 13 10 8 13 Pass Pass 10 Pass Pass Reject Level 10 Pass / Fail? Pass If Failed - Remove By: -0.514 -0.2175 -0.42375 -0.371-0.29813 -0.25063 -0.39063 Statistical Data: -0.09688 -0.25375 0.0775 -0.0075 0.0575 0.11125 0.033 -0 45 -0.02813 -0.00562 -0.5 -0.35 -0.261 -0.057 -0.45 -0.2 Mean (Average Proof) -0.275 -0.4 -0.05 -0.20.05 0.025 0.05 0.2 0.2 0.507901 0.05 0.94601 0.406841 0.853307 0.530053 -0.025 -0.3 0.514972 0.691759 0.653057 Median 0.573869 0.518451 0.423898 0.743919 1.049506 0.601835 0.165519 0.257963 0.657946 0.567305 0.894935 0.673326 0.758711 0.426484 0.728133 0.265196 0.280956 0.47853 Standard Deviation 0.268791 0.329326 0.553416 1.101462 0.17969 0.575642 | 0.432893 | 0.321835 | 0.362205 -0.33 28 -1.83692 -0.0984 0.453368 0.936196 1.658663 0.309276 0.03005 Sample Variance -0.12917 -1.34021 -0.90536 -0.34772 -1.00836 -2.31706 -0.11298 0.008438 -0.10984 -1.35 -6.05 -0.48517 0.582796 -2.3 -1.95 -2.05 Skewness -2.7 -1.85 -2.45 -1.1 -2.75 -6.2 -1.65 -1.6 -1.2 0.45 d.25 -1.75 -2.55 3.05 -2.05 1.55 1.05 2.4 3.9 Minimum 1.8 1.45 0.95 1.6 3.95 1.35 1.4 50 50 1.45 2.75 80 1.1 80 80 80 80 Maximum 80 80 0.17104 0.094334 0.165551 0.233556 0.115376 0.127708 0.153943 0.145331 0.189894 0.114601 0.117957 0.210524 0.115623 0.144844

80

32

50

Count

Confidence Level(95.0%)

50

0.191357 0.215623 0.237215 0.126248

Meter Code 033 American AL175

Code & Year:	1985
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	1
-1.2 to4	11
4 to .4	25
.4 to 1.2	12
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	50

1986
Number
0
0
1
3
14
29
2
0
1
0
0
50

Code & Year:	1987
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	7
4 to .4	18
.4 to 1.2	5
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1988
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	20
4 to .4	39
.4 to 1.2	19
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1989
	.
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	9
4 to .4	27
.4 to 1.2	10
1.2 to 2.0	3
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	50

Code & Year:	1990
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	13
4 to .4	57
.4 to 1.2	10
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1991
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	3
-1.2 to4	7
4 to .4	43
.4 to 1.2	21
1.2 to 2.0	4
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1992
Data Range	Number
LT -3.6	1
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	3
-1.2 to4	8
4 to .4	40
.4 to 1.2	26
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	1
Total	80

r
0
0
0
0
14
41
24
1
0
0
0
80

Code & Year:	1994
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	0
-1.2 to4	18
4 to .4	49
.4 to 1.2	11
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Meter Code 033 American AL175

Code & Year:	1995
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	4
-1.2 to4	21
4 to .4	45
.4 to 1.2	7
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

1996
Number
0
0
0
3
35
33
8
1
0
0
0
80

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	5
-1.2 to4	32
4 to .4	29
.4 to 1.2	10
1.2 to 2.0	2
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	1
Total	80

1998 l
Number
0
0
1
1
39
35
3
1
0
0
0
80


1 2 3/	4000
Code & Year:	1999
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	29
4 to .4	40
.4 to 1.2	10
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

2001
Number
IAMILIDEI
1
0
0
5
36
32
3
2
0
1
0
80

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	20
4 to .4	28
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	50

Code & Year:	2005
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	4
-1.2 to4	21
4 to .4	25
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	C
GT 3.6	
Total	50

Total
Number
2
0
11
37
354
635
182
17
1
1
2
1242



American AL175

Year 2007

American AL175	rear 2007			······					
175 CFH		Control Grou	up-Installed Y			T			
Code: 33A	1992	1993	1994	1997					
Sample Plan	Reduced	Reduced	Reduced	Reduced	1				
Sample Size	80	50	50	32					
Original Population	5435	2267	2833	975					
# of Slow Failures	0	0	0	0					
# of Fast Failures	2	0	1	0					
Total Failures:	2	0	1	0					
Accept Level	10	7	7	5					
Reject Level	13	10	10	8					
Pass / Fail?	Pass	Pass	Pass	Pass					
If Failed - Remove By:									
Statistical Data:				0.000405					
Mean (Average Proof)	0.106875	0.041	1	-0.303125					
Median	0.075	l .	-0.05						
Standard Deviation	0.732463		0.602411	1					
Sample Variance	0.536503		0.362899						
Skewness	1.248511		1.054728	1					
Minimum	-1.3	1		E .	1				
Maximum	3.25		2.15	1	1 1				
Count	80	1	50	1	1				
Confidence Level(95.0%)	0.163002	0.173244	0.171203	0.188418	L		1	<u></u>	•

Meter Code 33A American AL175


Orde 8 Voor	1992	#
Code & Year:	1992	77*
Data Range	Number	
LT -3.6	0	
-3.6 to -2.8	0	
-2.8 to2	0	
2 to -1.2	1	
-1.2 to4	15	
4 to .4	43	-
.4 to 1.2	17	_
1.2 to 2.0	2	
2.0 to 2.8	1]
2.8 to 3.6	1	
GT 3.6	C	1
Total	80	

Code & Year:	1993
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	9
4 to .4	29
.4 to 1.2	8
1.2 to 2.0	3
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	50

1994
Number
0
0
0
1
11
31
5
1
1
0
0
50

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	12
4 to .4	16
.4 to 1.2	2
1.2 to 2.0	
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	4
-1.2 to4	47
4 to .4	119
.4 to 1.2	32
1.2 to 2.0	7
2.0 to 2.8	2
2.8 to 3.6	1
GT 3.6	0
Total	212



Year 2007 American 5B225 Control Group-Installed Year 225 CFH 1996 1993 1995 1987 1988 1989 1990 1986 Code: 041 Single Single Single Single Single Single Single Single Sample Plan 50 50 32 32 32 32 32 Sample Size 32 343 423 170 127 55 Original Population 176 98 119 0 0 1 2 0 1 0 1 # of Slow Failures 0 0 3 1 0 0 # of Fast Failures 2 0 0 2 2 1 4 3 0 Total Failures: 7 7 5 5 5 5 5 5 Accept Level 8 6 6 8 6 6 6 6 Reject Level Pass Pass **Pass** Pass Pass / Fail? Pass Pass Pass Pass If Failed - Remove By: Statistical Data: -0.516 -0.353125 -0.31 0.217188 -0.254688 -0.007812 0.051563 -0.1 Mean (Average Proof) -0.3 -0.55 0.05 0.1 -0.375 0.025 -0.15 -0.125Median 0.74854 0.676199 0.542052 1.387072 0.992553 1.114963 0.954878 1.1733162 Standard Deviation 0.457245 0.29382 0.560313 1.923969 1.243143 0.985161 1.3766709 0.911792 Sample Variance 0.262687 0.956462 0.3314 0.250575 -0.437997 0.608773 0.197568 -0.309327 Skewness -1.9 -1.65 -2.1 -2.2 -2.1-1.95 -1.65 -3.75Minimum 1.3 0.95 1.55 2.05 3.25 3.05 2.6 Maximum 50 32 50 32 32 32 32 32 Count 0.357853 | 0.269878 | 0.192174 | 0.154049 0.500093 0.401987 0.34427 0.4230256

Confidence Level(95.0%)

Meter Code 041 American 5B-225

Code & Year:	1986
Data Range	Number
LT -3.6	1
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	10
4 to .4	11
.4 to 1.2	5
1.2 to 2.0	0
2.0 to 2.8	2
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1987
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	4
-1.2 to4	7
4 to .4	11
.4 to 1.2	6
1.2 to 2.0	4
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1988
Data Range	Number
ĻT -3.6	0
-3.6 to -2.8	0
-2.8 to2	<u>1</u> 5
2 to -1.2	
-1.2 to4	3
4 to .4	12
.4 to 1.2	5
1.2 to 2.0	3
2.0 to 2.8	3
2.8 to 3.6	
GT 3.6	0
Total	32
-1.2 to4 4 to .4 4 to 1.2 1.2 to 2.0 2.0 to 2.8 2.8 to 3.6 GT 3.6	12

Code & Year:	1989
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	3
-1.2 to4	6
4 to .4	10
.4 to 1.2	8
1.2 to 2.0	3
2.0 to 2.8	0
2.8 to 3.6	1
GT 3.6	0
Total	32


Code & Year:	1990
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2 2 8
2 to -1.2	2
-1.2 to4	
4 to .4	9
.4 to 1.2	9
1.2 to 2.0	2 0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1993
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	13
4 to .4	15
.4 to 1.2	0
1.2 to 2.0	1
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1995
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	19
4 to .4	23
.4 to 1.2	3
1.2 to 2.0	2
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	50

Code & Year:	1996
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	4
-1.2 to4	27
4 to .4	17
.4 to 1.2	2
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	50

Code & Year:	Total
Data Range	Number
LT -3.6	1
-3.6 to -2.8	0
-2.8 to2	4
2 to -1.2	26
-1.2 to4	93
4 to .4	108
.4 to 1.2	38
1.2 to 2.0	15
2.0 to 2.8	3
2.8 to 3.6	4
GT 3.6	0
Total	292



Year 2007 Rockwell R250 Control Group-Installed Year 250 CFH 1989 1990 1995 Code: 057 1988 Single Single Single Single Sample Plan 50 32 80 Sample Size 80 261 479 Original Population 638 568 2 # of Slow Failures 11 12 3 3 1 # of Fast Failures 1 5 12 13 Total Failures: 5 10 10 7 Accept Level 8 6 11 Reject Level 11 Pass / Fail? Fail Fail Pass **Pass** June 2009 June 2009 If Failed - Remove By: Statistical Data: 0.032813 -0.575625 -0.62875 -0.433 Mean (Average Proof) -0.525 -0.3 -0.25 -0.2 Median 1.68679 1.453798 1.10724 1.350246 Standard Deviation 1.225981 2.84526 1.823164 2.11353 Sample Variance -0.912486 -0.560931 0.962556 -0.82397 Skewness -5.55 -3.35 -4.35 -4.1 Minimum 4.4 2.15 2.25 2.9 Maximum 80 50 32 80 Count 0.608153 0.323527 0.314674 0.300483 Confidence Level(95.0%)

Year 2007

Meter Code 057 Rockwell R250


Code & Year:	1988
Data Range	Number
LT -3.6	4
-3.6 to -2.8	3
-2.8 to2	4
2 to -1.2	9
-1.2 to4	17
4 to .4	25
.4 to 1.2	16
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	1
GT 3.6	0
Total	80

Code & Year:	1989
Data Range	Number
LT -3.6	3
-3.6 to -2.8	3
-2.8 to2	6
2 to -1.2	11
-1.2 to4	19
4 to .4	21
.4 to 1.2	10
1.2 to 2.0	6
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1990
Data Range	Number
LT -3.6	1
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	8
-1.2 to4	11
4 to .4	19
.4 to 1.2	6
1.2 to 2.0	2
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	50

Code & Year:	1995
Data Range	Number
LT -3.6	0
-3.6 to -2.8	2
-2.8 to2	0
2 to -1.2	1
-1.2 to4	10
4 to .4	9
.4 to 1.2	7
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	3
Total	32

Code & Year:	Totals
Data Range	Number
LT -3.6	8
-3.6 to -2.8	8
-2.8 to2	12
2 to -1.2	29
-1.2 to4	57
4 to .4	74
.4 to 1.2	39
1.2 to 2.0	9
2.0 to 2.8	2
2.8 to 3.6	1
GT 3.6	3
Total	242



Year 2007 American AC250 Control Group-Installed Year 250 CFH 1998 1999 2001 2003 2005 1994 1995 1996 1997 1989 1990 1991 1992 1993 1988 1985 1986 1987 Code: 078 Reduced Sample Plan Reduced 50 80 80 80 80 80 80 80 32 32 50 80 50 80 32 80 80 80 Sample Size 2260 7615 8997 6850 5025 5667 9742 4721 143 727 2506 3405 4854 2891 4479 3854 4410 1021 Original Population 0 0 0 2 n ٥ 0 0 n 0 0 0 0 2 0 # of Slow Failures 0 0 Λ 0 0 0 Λ 0 # of Fast Failures Ω 0 0 0 0 1 2 0 0 0 0 3 0 Total Failures: 0 10 10 10 7 10 10 10 5 7 10 10 5 10 10 Accept Level 5 10 13 13 13 10 13 13 10 13 13 8 13 10 8 13 13 8 13 Reject Level Pass / Fail? Pass Pass Pass If Failed - Remove By: 0.01375 Statistical Data: -0.277 -0.27313 -0.21188 -0.2575 -0.276 -0.16875 -0.30313 -0.22 -0.1125 -0.09219 -0.78375 -0.56188 -0.996 -0.63625 -0.52688 -0.07813 -0.095 Mean (Average Proof) -0.225 -0.225 -0.2 -0.2 -0.2 -0.275-0.15 -0.2 -0.2 -0.65 -0.775 -0.55 -1.05-0.2-0.7 -0.125 Median 0.4574 0.448623 0.671492 0.534275 0.415909 0.466808 0.826585 | 0.442865 | 0.505403 | 0.542403 0.509116 0.879728 0.473525 0.777624 0.525652 0.579883 0.417932 0.665877 Standard Deviation 0.172981 0.21791 0.209215 | 0.201262 | 0.450902 0.285449 0.683243 0.196129 0.255433 0.294201 0.259199 0.77392 0.224226 0.604699 0.27631 0.336264 0.174667 0.443392 Sample Variance 0.027309 0.104201 -1.69438 -0.39525 3.605062 -0.36822 0.048867 -0.38088 -0.21421 1.707879 0.172843 3.606258 0.877857 -0.334 0.416486 -0.12864 2.141037 0.953233 -1.35 1.25 Skewness -2.75 -1.4 -1.5 -1.9 -2.1 -1.7 -3.85 -1.3 -0.95 -0.9 -1.15 -1.65 -2.15-1.7 Minimum 0.65 4.3 0.9 1.05 1.3 0.95 0.95 1.25 2.55 0.5 2.9 0.9 1.45 5.15 0.85 3.6 Maximum 80 50 80 80 80 80 80 80 50 32 32 50 80 80 80 32 80 Count 0.15967 0.143634 0.120706 0.113298 0.101789 0.099836 0.149433 0.118897 0.1182 0.103883 0.150681 0.148184 0.129047 0.195774 0.105378 0.173052 0.149389 0.298016 Confidence Level(95.0%)

Meter Code 078 American AC250

Code & Year:	1985
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	9
4 to .4	21
.4 to 1.2	2
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

1986
Number
0
0
0
0
24
45
10
0
0
1
0
80

Code & Year:	1987
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
- 2 to -1.2	12
-1.2 to4	43
4 to .4	22
.4 to 1.2	2
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1988
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	7
-1.2 to4	45
4 to .4	23
.4 to 1.2	1
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	1
Total	80

Code & Year:	1989
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	15
-1.2 to4	49
4 to .4	15
.4 to 1.2	0
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

	Code & Year:	1990
I		
١	Data Range	Number
	LT -3.6	1
	-3.6 to -2.8	0
١	-2.8 to2	1
	2 to -1.2	8
	-1.2 to4	38
	4 to .4	28
	.4 to 1.2	3
	1.2 to 2.0	0
	2.0 to 2.8	1
	2.8 to 3.6	0
	GT 3.6	0
	Total	80

Code & Year:	1991
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	17
-1.2 to4	26
4 to .4	6
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	50

1992
Number
0
0
0
1
10
15
4
1
0
1
0
32

Code & Year:	1993
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	8
4 to .4	19
.4 to 1.2	5
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1994
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	14
4 to .4	32
.4 to 1.2	3
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	50

Meter Code 078 American AC250

Code & Year:	1995
Code & Tear.	1000
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	24
4 to .4	46
.4 to 1.2	8
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1996
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	1
-1.2 to4	29
4 to .4	42
.4 to 1.2	7
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	25
4 to .4	49
.4 to 1.2	4
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80

Code & Year:	1998
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	28
4 to .4	47
.4 to 1.2	3
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	80


Code & Year:	1999
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	21
4 to .4	52
.4 to 1.2	3
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	1
Total	80

2001
Number
0
0
2
1
20
53
4
0
0
0
0
80

2003
Number
0
0
0
1
17
31
1
0
0
0
0
50

- 1		
١	Code & Year:	2005
	Data Range	Number
	LT -3.6	0
	-3.6 to -2.8	0
	-2.8 to2	
	2 to -1.2	1
	-1.2 to4	12
	4 to .4	54
	.4 to 1.2	12
	1.2 to 2.0	1
	2.0 to 2.8	
	2.8 to 3.6	
	GT 3.6	(
	Total	80

Code & Year:	Totals
Data Dance	Number
Data Range	Number
LT -3.6	1
-3.6 to -2.8	0
-2.8 to2	6
2 to -1.2	73
-1.2 to4	442
4 to .4	600
.4 to 1.2	73
1.2 to 2.0	6
2.0 to 2.8	1
2.8 to 3.6	2
GT 3.6	2
Total	1206



Rockwell R200	Year 2007						
200 CFH		Control Gro	up-Installed Y	ear			
Code: 079	1985	1996	1997				
Sample Plan	Single	Single	Single				
Sample Size	50	32	3*				
Original Population	300	256	3				
# of Slow Failures	0	0	0				
# of Fast Failures	5	0	0				
Total Failures:	5	0	0				
Accept Level	7	5	1				
Reject Level	8	6	2				
Pass/ Fail?	Pass	Pass	Pass				
If Failed - Remove By:			Exhaust				
Statistical Data:							
Mean (Average Proof)	0.563		-0.333333				
Median	0.45			1 1			
Standard Deviation	0.878996			L .			
Sample Variance	0.772634		0.660833	1			
Skewness	0.790697	0.336299		1			
Minimum	-1	-1.5	-1.25				
Maximum	2.75		0.3	1			
Count	50		3	1			
Confidence Level(95.0%)	0.249808	0.208325	2.019397		<u> </u>	<u> </u>	 <u></u>

^{*} Population less than required 32 minimum sample size - all meters to be changed - Single Sampling Plan For Normal Inspection used to obtain sample size to determine if control passed or failed.


Meter Code 079 Rockwell R200

Code & Year:	1985
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	4
4 to .4	20
.4 to 1.2	16
1.2 to 2.0	5
2.0 to 2.8	5
2.8 to 3.6	0
GT 3.6	0
Total	50

Code & Year:	1996
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	13
4 to .4	15
.4 to 1.2	0
1.2 to 2.0	
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	0
4 to .4	2 0
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	3

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	17
4 to .4	37
.4 to 1.2	18
1.2 to 2.0	5
2.0 to 2.8	5
2.8 to 3.6	0
GT 3.6	0
Total	85



Test Year 2007 American AL1000 Control Group-Installed Year 1000 CFH 2005 2003 2002 2000 2001 1998 1999 1997 Code: 014 Single Single Single Single Single Single Single Single Sample Plan 50 50 13 32 20 20 32 13* Sample Size 488 60 281 257 105 175 73 127 Original Population 1 2 1 1 0 2 1 0 # of Slow Failures 1 1 0 1 0 0 0 # of Fast Failures 3 2 1 1 1 2 1 Total Failures: 7 7 5 2 5 3 3 2 Accept Level 8 8 6 3 6 4 4 3 Reject Level Pass Pass Pass **Pass Pass Pass** Pass Pass / Fail? Pass Exhaust If Failed - Remove By: Statistical Data: -0.622-0.10625 -0.734615 -0.761 -0.51 -0.423438 -0.334615 -0.84 Mean (Average Proof) -0.575 -0.7-0.85 -0.075-0.45 -0.675 -0.525Median 0.804515 | 0.957158 0.786568 0.99172 0.586403 0.937746 0.849861 0.864914 Standard Deviation 0.916152 0.61869 0.983508 0.647244 0.879368 0.343868 0.722263 0.748077 Sample Variance 1.410935 0.227796 -0.13949 -0.290716 1.231541 0.192046 -1.035523 -0.43584 Skewness -2.7 -2.75 -2.35 -1.9 -2.15-2.55 -3.25 -1.8 Minimum 2.15 3.25 3.45 0.75 0.95 0.85 1.2 Maximum 50 50 32 13 32 20 20 13 Count 0.522663 | 0.397747 | 0.438879 | 0.211421 | 0.357553 | 0.486163 | 0.272021 0.22354 Confidence Level(95.0%)

^{*} Control group in 10th year of service - maximum service period - all meters to be removed/tested. Sample size based on population was used to determine if group passed/failed in it's last year of service.

Meter Code 014 American AL1000

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	2
4 to .4	6
.4 to 1.2	2
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	13

Code & Year:	1998
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	5
2 to -1.2	
-1.2 to4	8
4 to .4	4
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

Code & Year:	1999
	Marianhan
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	0
2 to -1.2	1
-1.2 to4	15
4 to .4	3
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20
1	

2000
Number
0
0
1
2
14
11
4
0
0
0
0
32


2001
Number
0
0
0
3
7
15
6
0
0
1
0
32

Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	1
-1.2 to4	6
4 to .4	4
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	13

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	13
-1.2 to4	21
4 to .4	11
.4 to 1.2	2
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	1
GT 3.6	0
Total	50

Code & Year:	2005
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	9
-1.2 to4	18
4 to .4	20
.4 to 1.2	1
1.2 to 2.0	C
2.0 to 2.8	1
2.8 to 3.6	
GT 3.6	C
Total	50
<u> </u>	W

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	7
2 to -1.2	37
-1.2 to4	91
4 to .4	74
.4 to 1.2	17
1.2 to 2.0	0
2.0 to 2.8	1
2.8 to 3.6	2
GT 3.6	0
Total	230



Test Year 2007 Actaris 800A Control Group-Installed Year 800 CFH 2002 2003 Code 016 Sample Plan Single Single 2 Sample Size 20 98 3 Original Population 0 # of Slow Failures 1 0 0 # of Fast Failures 0 1 Total Failures: 3 0 Acept Level 1 Reject Level Pass / Fail ? **Pass** Pass If Failed - Remove By: Statistical Data: -0.08 0.425 Mean (Average Proof) 0.175 0.425 Median 0.808572 0.459619 Standard Deviation 0.21125 0.653789 Sample Variance NA -2.521437 Skewness -2.9 0.1 Minimum 0.75 0.65 Maximum 20 Count 0.378424 4.129517 Confidence Level(95.0%)


Year 2007

Meter Code 016 Actaris 800A

Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	0
2 to -1.2	1
-1.2 to4	1
4 to .4	13
.4 to 1.2	4
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	0
4 to .4	1
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0 2
Total	2

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	0
2 to -1.2	1
-1.2 to4	1
4 to .4	14
4 to 1.2	5
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	22




Test Year 2007 Actaris 800A Control Group-Installed Year 800 CFH Code 16T 2002 Sample Plan Single 2 Sample Size Original Population 8 # of Slow Failures 0 0 # of Fast Failures 0 Total Failures: Acept Level 0 Reject Level Pass / Fail ? Pass If Failed - Remove By: Statistical Data: 0.275 Mean (Average Proof) 0.275 Median 0.035355 Standard Deviation 0.00125 Sample Variance NA Skewness 0.25 Minimum 0.3 Maximum Count 0.317655 Confidence Level(95.0%)

Meter Code 16T Actaris 800A

Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	0
4 to .4	2
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	0 2 0
4 to .4	2
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2



Actaris 1000A Test Year 2007 Control Group-Installed Year 1000 CFH 2003 2002 Code 017 Single Sample Plan Single 8 Sample Size 20 Original Population 106 20 # of Slow Failures 0 0 # of Fast Failures 0 0 0 Total Failures: 0 3 1 Accept Level Reject Level 4 2 Pass / Fail ? Pass Pass If Failed - Remove By: Statistical Data: -0.375 -0.15625 Mean (Average Proof) -0.325 -0.3 Median 0.467777 0.537479 Standard Deviation 0.218816 0.288884 Sample Variance -0.981042 0.965504 Skewness -0.7 -1.5 Minimum 0.35 0.85 Maximum 20 Count 0.218927 0.449344 Confidence Level(95.0%)


Year 2007

Meter Code 017 Actaris 1000A

Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	5
4 to .4	13
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

Code & Year:	2003
Data Danas	Niumbaa
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	3
4 to .4	4
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

	······································
Çode & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2 8
-1.2 to4	8
4 to .4	17
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	28



Actaris 1000A Test Year 2007 Control Group-Installed Year 1000 CFH Code 17T 2002 Single Sample Plan 2 Sample Size Original Population 8 # of Slow Failures 0 # of Fast Failures 0 Total Failures: 0 Accept Level 0 Reject Level Pass / Fail ? Pass If Failed - Remove By: Statistical Data: -0.2 Mean (Average Proof) -0.2 Median 0.424264 Standard Deviation 0.18 Sample Variance NA Skewness -0.5 Minimum 0.1 Maximum Count


3.811861

Confidence Level(95.0%)

Meter Code 17T Actaris 1000A

Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	1
4 to .4	1
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	1
4 to .4	1
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0 2
Total	2



American AL 1400 Test Year 2007

American AL 1400	Test Year 200	/							
1400 CFH		Control Gro	up-Installed Y	ear					
Code: 019	1997	1998	1999	2000	2001	2002	2003	2005	
Sample Plan	Single	Single	Single	Single	Single	Single	Single	Single	
Sample Size	2*	2	2	2	8	8	8	8	
Original Population	5	8	6	7	19	16	28	42	
# of Slow Failures	0	0	0	0	0	0	0	0	
# of Fast Failures	0	0	0	0	0	0	0	0	
Total Failures:	0	0	0	0	0	0	0	0	
Accept Level	0	0	0	0	1	1	1	1	
Reject Level	1	1	1	1	2	2	2	2	
Pass / Fail?	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	
If Failed - Remove By:	Exhaust								
Statistical Data:							0.475	0.075	
Mean (Average Proof)	-1.925	-0.925	-1.3	1		-0.8	-0.175	-0.975	
Median	-1.925	-0.925	-1.3	-1.65	-0.125	-1	-0.325	-1	
Standard Deviation	0.035355	0.883883	0.212132	1	0.707612		0.977241	0.653015	
Sample Variance	0.00125	0.78125	0.045	1 1	0.500714		0.955	0.426429	
Skewness	NA	NA	NA	NA	-0.270948		-0.129193		ľ
Minimum	-1.95	-1.55	-1.45	1	-1.4	-2	-1.85		
Maximum	-1.9	-0.3	-1.15	-1.6	0.6	1.25	1.3	-0.1	
Count	2	2	2	2	8	8	8	8	
Confidence Level(95.0%)	0.317655								

^{*} Control group in 10th year of service - maximum service period - all meters to be removed/tested. Sample size based on population was used to determine if group passed/failed in it's last year of service.

Meter Code

019

American AL 1400

Code & Year:	1997	
Data Range	Number	
LT -3.6	0	
-3.6 to -2.8	0	
-2.8 to2	0	
2 to -1.2	2	
-1.2 to4	0	
4 to .4	0	
.4 to 1.2	0	
1.2 to 2.0	0	
2.0 to 2.8	0	
2.8 to 3.6	0	
GT 3.6	0	
Total	2	

Code & Year:	1998
Doto Bongo	Number
Data Range	·
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	0
4 to .4	1
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2

1999
Number
0
0
0
1
1
0
0
0
0
0
0
2

Code & Year:	2000
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	0
4 to .4	0
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2


Code & Year:	2001
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	1
4 to .4	4
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	2
4 to .4	2
.4 to 1.2	0
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	2
4 to .4	
.4 to 1.2	1
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2005
Data Range	Number
LT -3.6	C
-3.6 to -2.8	C
-2.8 to2	C
2 to -1.2	4
-1.2 to4	2 2
4 to .4	2
.4 to 1.2	
1.2 to 2.0	
2.0 to 2.8	C
2.8 to 3.6	
GT 3.6	
Total	

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	16
-1.2 to4	8
4 to .4	12
.4 to 1.2	2 2
1.2 to 2.0	
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	40




Rockwell R800 Year 2007 800 CFH Control Group-Installed Year Code: 053 2005 Sample Plan Single Sample Size 2 Original Population 3 # of Slow Failures 0 # of Fast Failures 0 Total Failures: Accept Level 0 Reject Level Pass / Fail? Pass If Failed - Remove By: Statistical Data: Mean (Average Proof) -0.825 -0.825 Median Standard Deviation 1.166726 Sample Variance 1.36125 Skewness NA -1.65 Minimum Maximum 0 Count 10.48262 Confidence Level(95.0%)

Meter Code 053 Rockwell R800

Code & Year:	2005	Code & Yea
Data Range	Number	Data Rang
LT -3.6	0	LT -3.6
-3.6 to -2.8	0	-3.6 to -2.
-2.8 to2	0	-2.8 to2
2 to -1.2	1	2 to -1.2
-1.2 to4	0	-1.2 to4
4 to .4	1	4 to .4
.4 to 1.2	0	.4 to 1.2
1.2 to 2.0	0	1.2 to 2.0
2.0 to 2.8	0	2.0 to 2.8
2.8 to 3.6	0	2.8 to 3.6
GT 3.6	0	GT 3.6
Total	2	Total

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	0
4 to .4	1
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2



Rockwell #3 Emco Year 2007 1200 CFH Control Group-Installed Year Code: 056 1997 2000 2001 1999 2002 2003 2005 Sample Plan Single Single Single Single Single Single Single Sample Size 8* 8 8 8 13 13 13 Original Population 19 41 47 58 62 79 41 # of Slow Failures 0 0 0 0 0 0 0 # of Fast Failures 0 ٥ 0 0 0 0 0 Total Failures: 0 0 0 0 0 0 0 Accept Level 1 1 1 2 2 2 Reject Level 2 2 2 2 3 3 3 Pass / Fail? Pass Pass Pass Pass Pass Pass Pass If Failed - Remove By: Exhaust Statistical Data: -0.3375 -1.05625 -0.6875 -0.469231 -0.061538 0.173077 Mean (Average Proof) -0.825 -0.325-0.875 Median -0.8 -0.925 -0.40.05 0.4 1.064274 0.468613 0.895126 1.057225 0.951786 1.123353 Standard Deviation 0.656288 1.117724 0.905897 1.132679 0.219598 0.430714 0.80125 Sample Variance 1.261923 0.043359 -0.711789 0.152625 0.485979 Skewness 0.589381 0.258735 -0.38631 Minimum -1.85 -1.85-1.8 -1.95-1.7 1.35 -0.55 0.3 1.95 1.9 1.9 Maximum 0.65 Count 13 13 13 0.889755 0.39177 | 0.548671 | 0.748344 | 0.638875 | 0.575159 | 0.678836 Confidence Level(95.0%)

^{*} Control group in 10th year of service - maximum service period - all meters to be removed/tested. Sample size based on population was used to determine if group passed/failed in it's last year of service.

Year 2007

Meter Code 056 Rockwell #3 Emco

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	2
4 to .4	2
.4 to 1.2	1
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	1999
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	5 0
4 to .4	0
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8


Code & Year:	2000
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
- 2 to -1.2	2 5
-1.2 to4	
4 to .4	1
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2001	Code & Year:	2002
Data Range	Number	Data Range	Number
LT -3.6	0	LT -3.6	0
-3.6 to -2.8	0	-3.6 to -2.8	0
-2.8 to2	0	-2.8 to2	0
2 to -1.2	2	2 to -1.2	3
-1.2 to4	3	-1.2 to4	3
4 to .4	1	4 to .4	5
.4 to 1.2	2	.4 to 1.2	1
1.2 to 2.0	0	1.2 to 2.0	1
2.0 to 2.8	0	2.0 to 2.8	0
2.8 to 3.6	0	2.8 to 3.6	0
GT 3.6	0	GT 3.6	0
Total	8	Total	13

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0 2 3 5 2
2 to -1.2	2
-1.2 to4	3
4 to .4	5
.4 to 1.2	2
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	13

Code & Year:	2005
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	3
4 to .4	3 3 5
.4 to 1.2	5
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	13

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	15
-1.2 to4	24
4 to .4	17
.4 to 1.2	11
1.2 to 2.0	4
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	71



750 CFH Control Group-Installed Year Code: 058 1997 1998 1999 2000 2001 2002 2003 2005 Sample Plan Single Single Single Single Single Single Single Single Sample Size 20* 20 20 32 32 20 80 32 Original Population 96 137 113 172 276 126 527 265 0 0 1 0 0 0 1 0 0 0 0 2 0 1 0 1 Total Failures: 0 0 2 2 1 0 0 1

Rockwell R750

Year 2007

of Slow Failures # of Fast Failures Accept Level 3 3 3 5 5 3 10 Reject Level 4 4 6 4 11 6 Pass / Fail? Pass Pass Pass Pass Pass Pass Pass Pass If Failed - Remove By: Exhaust Statistical Data: -0.1725 -0.41 -0.28 0.18125 0.114063 -0.4125 0.265625 -0.0925 Mean (Average Proof) Median -0.15 -0.5 -0.1 0.075 -0.25 0.175 -0.15 0.1 1.003522 0.80093 1.025321 0.704421 0.863511 0.631539 0.949571 0.728613 Standard Deviation 0.398842 0.641489 1.051283 0.530877 Sample Variance 0.745651 0.901684 1.007056 0.496209 0.192841 -0.531942 -0.50751 1.556648 0.639288 0.103187 0.340786 2.313207 Skewness Minimum -1.95-1.5 -2.1 -1.35 -1.25-1.05 -1.5 -2.71.45 0.75 2.05 1.75 3.95 3.65 Maximum Count 20 20 20 32 32 20 32 80 0.404136 | 0.29557 | 0.444413 | 0.361808 | 0.288766 | 0.479865 | 0.262693 | 0.156761 Confidence Level(95.0%) * Control group in 10th year of service - maximum service period - all meters to be removed/tested. Sample size based on

population was used to determine if group passed/failed in it's last year of service.

Meter Code 058 Rockwell R750

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	4
4 to .4	6
.4 to 1.2	7
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

Code & Year:	1998
_	
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	9
4 to .4	6
.4 to 1.2	3
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

Code & Year:	1999
	_
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	3
-1.2 to4	4
4 to .4	9
.4 to 1.2	2
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

2000
Number
0
0
0
1
10
10
9
0
1
0
1
32


Code & Year:	2001
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	7
4 to .4	15
.4 to 1.2	5
1.2 to 2.0	4
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	3
-1.2 to4	5
4 to .4	9
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	20

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	5
4 to .4	18
.4 to 1.2	4
1.2 to 2.0	5
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	32

Code & Year:	2005
Data Range	Number
LT -3.6	0
-3.6 to -2.8	O
-2.8 to2	C
2 to -1.2	2
-1.2 to4	26
4 to .4	36
.4 to 1.2	15
1.2 to 2.0	C
2.0 to 2.8	C
2.8 to 3.6	C
GT 3.6	1
Total	80

Code & Year:	Total
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	2
2 to -1.2	15
-1.2 to4	70
4 to .4	109
.4 to 1.2	46
1.2 to 2.0	10
2.0 to 2.8	2
2.8 to 3.6	0
GT 3.6	2
Total	256



American AL 800 Year 2007 800 CFH Control Group-Installed Year Code: 076 1997 1998 1999 2000 2001 2002 2003 2005 Sample Plan Single Single Single Single Single Single Single Single 2* Sample Size 2 2 8 13 8 20 8 Original Population 7 49 10 4 32 60 36 121 # of Slow Failures 0 0 0 0 0 1 3 0 # of Fast Failures 0 0 0 0 0 0 0 1 Total Failures: ٥ 0 0 0 1 1 3 0 Accept Level 0 0 0 1 2 1 3 1 Reject Level 1 1 1 2 3 2 4 2 Pass / Fail? Pass Pass Pass Pass Pass Pass Pass Pass If Failed - Remove By: Exhaust Statistical Data: 0.3 -0.50625 -0.369231 -0.275 -0.89375 -0.6825 Mean (Average Proof) 0.15 -0.5125 Median 0.3 -0.275 0.15 -0.3 -0.675 -0.5 -0.525-0.6 0.424264 0.070711 0.035355 0.78031 1.010886 1.513614 0.861039 0.539014

0.18 0.608884

NA

-0.15

0.45

1.052553

0.45

0.63531 | 0.317655 | 3.811861 | 0.652356 | 0.610872 | 1.265413 | 0.402979 | 0.450627

0.00125

-0.3

-0.25

NA

0.005

0.25

0.35

NA

1.021891

-1.65

2.35

13

2.291027

1.588121 -1.842283 -0.945538

-4.3

0.7

0.290536

0.076057

-1.45

0.45

0.741388

-2.75

0.75

20

Standard Deviation

Confidence Level(95.0%)

Sample Variance

Skewness Minimum

Maximum Count

^{*} Control group in 10th year of service - maximum service period - all meters to be removed/tested. Sample size based on population was used to determine if group passed/failed in it's last year of service.

Meter Code 076 American AL800

Code & Year:	1997
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	0
4 to .4	2
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2

Code & Year:	1998
D	N I
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	0
4 to .4	2
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2

Code & Year:	1999
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	0
-1.2 to4	0
4 to .4	1
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	2

Code & Year:	2000
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	0
4 to .4	5
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8


Code & Year:	2001
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	6
4 to .4	4
.4 to 1.2	0
1.2 to 2.0	0
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	13

Code & Year:	2002
Data Range	Number
LT -3.6	1
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	4
4 to .4	1
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2003
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	3
2 to -1.2	1
-1.2 to4	8
4 to .4	7
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

Code & Year:	2005
Data Range	Number
LT -3.6	C
-3.6 to -2.8	
-2.8 to2	C
2 to -1.2	1
-1.2 to4	3
4 to .4	1 3 3
.4 to 1.2	1
1.2 to 2.0	C
2.0 to 2.8	C
2.8 to 3.6	C
GT 3.6	(
Total	8

Code & Year:	Totals
Data Range	Number
LT -3.6	1
-3.6 to -2.8	0
-2.8 to2	3
2 to -1.2	7
-1.2 to4	21
4 to .4	25
.4 to 1.2	5
1.2 to 2.0	0
2.0 to 2.8	1
2.8 to 3.6	0
GT 3.6	0
Total	63



Rockwell #4 Emco Year 2007 2250 CFH Control Group-Installed Year 2002 Code: 028 2003 2004 2005 Sample Plan Single Single Single Single Sample Size 13* 32 20 20 Original Population 73 104 184 126 # of Slow Failures 0 0 0 1 # of Fast Failures 0 0 0 0 Total Failures: 0 0 0 1 Accept Level 2 5 3 3 Reject Level 3 6 Pass / Fail? Pass Pass Pass Pass If Failed - Remove By: Exhaust Statistical Data: -0.9625 -0.2975 Mean (Average Proof) -0.719231 -0.4275 -0.675 -0.825 -0.275 Median -0.7 0.626012 0.988017 0.653105 1.113963 Standard Deviation 0.976178 0.426546 1.240914 0.391891 Sample Variance 0.430508 -0.313552 -0.801296 0.160186 Skewness -1.65 -2 -2.95 Minimum 1.7 0.55 1.45 -0.1 Maximum Count 13 20 20 20 0.378295 | 0.462406 | 0.305663 | 0.521351 Confidence Level(95.0%)

^{*} Control group in 5th year of service - maximum service period - all meters to be removed/tested. Sample size based on population was used to dertermine if group passed/failed in it's last year of service.

Meter Code 028 Rockwell #4 Emco


Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	3
-1.2 to4	8
4 to .4	1
.4 to 1.2	1
1.2 to 2.0	0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	13

Code & Year:	2003
Data Range	Number
LT -3.6	
	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	4
-1.2 to4	7
4 to .4	6
.4 to 1.2	2
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

2004
Number
0
0
0
6
8
11
3
4
0
0
Ó
32

Code & Year:	2005
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	0 3 3 8
2 to -1.2	3
-1.2 to4	3
4 to .4	
.4 to 1.2	4
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	20

Code & Year:	Total
-	
Data Range	Number
LT -3.6	0
-3.6 to -2.8	1
-2.8 to2	0
2 to -1.2	16
-1.2 to4	26
4 to .4	26
.4 to 1.2	10
1.2 to 2.0	6
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	85



Rockwell 10Emco Year 2007 Control Group-Installed Year 5000 CFH 2003 2005 Code: 061 2002 2004 Sample Plan Single Single Single Single 8 8* 8 13 Sample Size Original Population 18 24 36 70 # of Slow Failures 0 0 0 1 # of Fast Failures 0 0 0 0 0 0 0 1 Total Failures: 2 Accept Level 1 2 2 2 3 Reject Level Pass / Fail? Pass Pass Pass Pass If Failed - Remove By: Exhaust Statistical Data: 0.0875 -0.1375 -0.834615 Mean (Average Proof) -0.2125 -0.25 -0.075 -0.05 -0.9 Median 1.255203 | 1.348478 | 0.779079 0.950304 Standard Deviation 1.575536 1.818393 0.606964 0.903077 Sample Variance 1.54387 -0.28511 0.112973 -0.115442 Skewness -2.05 -1.9 -1.1 Minimum -2 1.7 1.5 0.8 Maximum Count 13 1.049376 1.127356 0.651326 0.574263 Confidence Level(95.0%)

^{*} Control group in 5th year of service - maximum service period - all meters to be removed/tested. Sample size based on population was used to dertermine if group passed/failed in it's last year of service.

Meter Code 061 Rockwell 10M Emco


Code & Year:	2002
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	2
-1.2 to4	2
4 to .4	1
.4 to 1.2	2
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2003
Data Range	Number
LT -3.6	
	0
-3.6 to -2.8	0
-2.8 to2	0
2 to -1.2	1
-1.2 to4	2
4 to .4	2
.4 to 1.2	0
1.2 to 2.0	3
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2004
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	0 0
2 to -1.2	0
-1.2 to4	3
4 to .4	2
.4 to 1.2	3
1.2 to 2.0	0 3 2 3 0
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	8

Code & Year:	2005
Data Range	Number
LT -3.6 -	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	4
-1.2 to4	5
4 to .4	2
.4 to 1.2	0
1.2 to 2.0	1
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	13

Code & Year:	Totals
Data Range	Number
LT -3.6	0
-3.6 to -2.8	0
-2.8 to2	1
2 to -1.2	7
-1.2 to4	12
4 to .4	7
.4 to 1.2	5
1.2 to 2.0	5
2.0 to 2.8	0
2.8 to 3.6	0
GT 3.6	0
Total	37



Louisville Gas & Electric

Regulator Inspection and Replacement Program
Report 2007



Year 2007 Regulator Inspection and Replacement Program

I. Progress Summary

During 2007, LG&E inspected or replaced a total of 22,869 gas pressure regulators as part of LG&E's regulator inspection and upgrade program. A total of 6,965 existing Schlumberger B42, National 496, or American 1213B gas pressure regulators remained in service. A total of 21,466 regulators were replaced with Schlumberger B42, National 496 and American 1213B regulators as part of LG&E's program to upgrade and standardize residential gas regulators. An additional 1,403 regulators were replaced as a result of either improper function of the regulator, damage/vandalism, service line replacement, or meter loop repairs. The distribution of the reasons for these regulator replacements is shown in Table 1 below.

Table 1: Year 2007 Regulator Change Reasons

Reason	Quantity
Regulator Replacement Program	21,466
Failed Lockup Test	24
Vent Leaking	108
Leak on Regulator	13
Routine Change During Meter Loop Repair	346
Could Not Adjust Pressure	12
Damage/Vandalism	60
Routine Change During Service Renewal	827
Test Site	12
Commercial / Security Bad	1
Total	<u>22,869</u>

For the time period of 2002 – 2007, a total of 75,777 regulator replacements have been made. This total represents 40% of the approximately 190,554 residential regulators that are expected to be replaced over the ten year period of the regulator replacement program.

II. Safety

As part of LG&E's regulator replacement activities, safety inspections were performed and "red-tags" were issued when deficiencies were found. The results of these safety inspections directly associated with LG&E's regulator replacement program are summarized in Table 2 below.

Table 2: Year 2007 Safety Inspection Results

Reason Q	<u>Quantity</u>	
Houseline Leak (includes lines to gas grills,	114	
pool heaters, appliance flexible hook-up lines, fireplace,		
etc.)		
Furnace Problem (internal leak, not burning correctly)	30	
Leak or Not Venting Properly (dryer, range, water heater)	27	
Flex Lines/Brass Connectors (not to code)	210	
Other Leaks	15	
Misc. (trees, bushes around meter, etc.)	7	
	Total	<u>403</u>

Additionally, Customer Surveillance Notices were issued to customers to correct outside deficiencies on their meter loop or exposed outside gas piping. The results of these safety inspections directly associated with LG&E's regulator replacement program are summarized in Table 3 below.

Table 3: Year 2007 Customer Surveillance Notices Issued

Reason	<u>Quantity</u>
	•
Corrosion / Rust On Outside Meter Loop & Associated Piping	2,204
Gas Meter In Contact With Soil / Pavement	18
Asphalt or Concrete Paving in Contact With Piping Entering Ground	25
Gas Piping Not Properly Supported	961
Meter Not Protected From Vehicular Damage	154
Customer Built Over Service Line / Around Meter	9
Tree / Shrubbery Growing Inside / Against Meter Loop	24
Total	<u>3,395</u>